## SONY

## UP971AD

The UP-971AD is a black and white HYBRID graphic printer that supports both analog and digital applications. This dual compatibility is especially critical as imaging systems make the transition from analog to digital technology. The UP-971AD has both an analog video input as well as a USB 2.0 high speed interface for digital printing. The UP-971AD offers an improved resolution of 325 dpi ensuring superb picture quality and faster print speed of about 8 seconds. As an extra convenience the UP-971AD uses the same media as the predecessor model - UPP-210HD and UPP-210SE. The UP-971AD is the ideal choice for medical black and white analog and digital applications such as ultrasound, mobile c-arm, and cardiac cath lab.



## **Specification**

Specifications	
Dimensions (W x H x D)	316 x 132.5 x 265 mm (12 1/2 x 5 1/4 x 10 1/2 inch)
Gradations	8 bits (256 levels) processing
Input Current	2.9 A to 1.2 A
Interface	Hi-Speed USB (USB 2.0) (x1) VIDEO INPUT: BNC type (X1) NTSC or PAL composite video signals 1.0Vp-p, 75ohm (NTSC/PAL automatically discriminated) VIDEO OUTPUT: BNC type (x1) Loop-through REMOTE: Stereo mini jack (x1)
Mass	7 kg (15lb 7oz)
Operating Humidity	20% to 80% (no condensation allowed)
Operating Temperature	5°C to 35°C (41°F to 95°F)
Paper Size	Paper width of 210 mm (8 1/4 inches)
Picture Area	DIGITAL: 600 x 200 mm (23 5/8 x 7 7/8 inch) (Max) VIDEO: STD NTSC: 182 x 144 mm PAL: 188 x 140 mm SIDE NTSC: 244 x 184 mm PAL: 244 x 183 mm
Picture Elements	Digital: 7680 x 2560 dots Video NTSC: 720 x 504 dots Video PAL: 720 x 604 dots

## SONY

Picture Memory	Digital: 2816 x 7680 x 8 bits Video: 6 frames (720 x 608 x 8 bits for one frame)
Power Requirements	AC 100 V to 240 V, 50/60 Hz
Printer Driver Software	Microsoft Windows XP 32/64, Vista 32/64, 7 32/64, 8 32/64
Printing Method	Direct thermal printing
Printing Time	Approx. 8 seconds/image (in standard mode)
Decel Co.	
Resolution	325 dpi
Storage and Transport Humidity	325 dpi 20% to 80%
Storage and Transport	